

MODERN FORMS

Dimming Compatibility

ID E2310054V0

Product Family:

Sku Tested: WS-40221

Related Models

Test Voltage: 120/277V

Control Type: ELV, TRIAC, MLV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	0.6%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	N/A	Flashing at all dimming levels
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	62.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	12.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	13.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	4.0%	Not Recommended
Cooper	AL Series	AAL06	120	48.0%	Flicker below 48%
Control4	Adaptive	C4-APD277	277	2.0%	
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	7.0%	
Lutron	Diva	DVELV-300P	120	4.0%	
Lutron	Maestro	MAELV-600	120	1.0%	
Lutron	Skylark	SELV-300P	120	4.0%	
Leviton	Illumatech	IPE04-1LZ	120	6.0%	
Lutron	Maestro	RRD-6NA	120	1.0%	
Leviton	SureSlide	6615-POW	120	17.0%	
Leviton	Decora	DSE06-10Z	120	3.0%	
Lutron	Caseta	PD-5NE	120	6.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at all dimming levels
Lutron	Homeworks	HQRD-6NA	120	1.0%	
Leviton	Renoir II	AWSMT-EBW	120	0.8%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	1.0%	
Leviton	Renoir II	AWSMT-EBW	277	7.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	12.0%	
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	6.0%	Flicker below 6%
Lutron	Diva	DVCL-153P	120	33.0%	Flicker below 33%; Turn on time >0.5s at the lowest dimming level
Legrand	Adorne Paddle	ADPD453LW2	120	16.0%	Flicker below 16%
Lutron	Ariadni	AYCL-153PH	120	5.0%	Flicker below 5%
Lutron	Skylark	SCL-153P-WH	120	21.0%	Flicker below 21%; Turn on time >0.5s at the lowest dimming level
Lutron	Maestro	MA-600-WH	120	7.0%	Flashing at low dimming level
Leviton	SureSlide	6674-POW	120	13.0%	Flicker below 13%
Lutron	Caseta	PD-6WCL	120	13.0%	Flicker below 13%
Legrand	Harmony	HCL453PW	120	7.0%	Flashing at low dimming level
Legrand	Radiant	RHCL453PW	120	5.0%	Flashing at low dimming level

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.