

WAC LIGHTING

Lotos R Retrofit

Adjustable Downlight 5CCT

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R6DRAK	A 50	9CS 2700K/3000K/3500K/4000K/5000K - 90	1270	1891	BK Black WT White

Example: **R6DRAK-A9CS-BK**

DESCRIPTION

Versatile and multifunctional, the Lotos R Downlights retrofit into 6-inch housings and are field adjustable up to 50 degrees in the regressed trim for quality, glare-free illumination. Offered as an All-In-One Five CCT Selectable luminaire, Lotos is ideal for recessed applications in multifamily homes, hotels, senior living and apartment buildings.

FEATURES


- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Installs into most standard 6" recessed cans
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction	Steel with frosted TIR lens
Power:	13W
Input:	120-277V,50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	TIR Lens
Rated Life:	50,000 Hours
Mounting:	Retrofit over a 6" recessed can
Finish:	Electrostatically Powder Coated: White, Black
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Title 24 JA8 Compliant, Airtight, IC



FINISHES:



LINE DRAWING

