

WAC LIGHTING

Simone

Bathroom Vanity & Sconce 3000K

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-79121 21"	3000K	BN Brushed Nickel	22W	1800	1178

Example: **WS-79121-BN**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Artfully framed illumination. Precisely cut and enveloped.

FEATURES

- Silk screen mitered tempered glass diffuser
- Conversion plate included to accommodate 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	54,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware, glass diffuser

REPLACEMENT PARTS

RPL-GLA-79120 - Glass




FINISHES:



Brushed Nickel

LINE DRAWING



WS-79121

WAC LIGHTING

Simone

Bathroom Vanity & Sconce 3000K

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-79130 30"	3000K	BN Brushed Nickel	34W	2500	1907

Example: **WS-79130-BN**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Artfully framed illumination. Precisely cut and enveloped.

FEATURES

- Silk screen mitered tempered glass diffuser
- Conversion plate included to accommodate 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	54,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware, glass diffuser

REPLACEMENT PARTS

RPL-GLA-79129 - Glass




FINISHES:



Brushed
Nickel

LINE DRAWING



WS-79130