

WAC LIGHTING

Fitzgerald

Wall Sconce

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-47108 8"	2700K	BK Black BN Brushed Nickel	13W	1100	714
	3000K				737
	3500K				597

Example: **WS-47108-35-BN**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Legendary style without pretense. Effortlessly classy

FEATURES

- Fabric shade with top and bottom etched acrylic diffuser
- 3CCT (2700K/3000K/3500K) selectable switch
- WS-47116 is ADA compliant, low profile design
- Option to pre-select color temperature or adjust in the field
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS


Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	54,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Dry Location Listed
Construction	Aluminum body, fabric diffuser

REPLACEMENT PARTS


RPL-DIF-47108-01 - Top Diffuser
RPL-DIF-47108-02 - Bottom Diffuser
RPL-SHA-47108-01 - Fabric Shade
RPL-SHA-47108-02 - Fabric Shade



FINISHES:



LINE DRAWING



WS-47108

WAC LIGHTING

Fitzgerald

Wall Sconce

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-47116 16"	2700K	BK Black BN Brushed Nickel	16W	1400	823
	3000K				882
	3500K				885

Example: **WS-47116-35-BN**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Legendary style without pretense. Effortlessly classy

FEATURES

- Fabric shade with top and bottom etched acrylic diffuser
- 3CCT (2700K/3000K/3500K) selectable switch
- WS-47116 is ADA compliant, low profile design
- Option to pre-select color temperature or adjust in the field
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS


Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	54,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Dry Location Listed
Construction	Aluminum body, fabric diffuser

REPLACEMENT PARTS


RPL-DIF-47116-01 - Top Diffuser
 RPL-DIF-47116-02 - Bottom Diffuser
 RPL-SHA-47116-01 - Fabric Shade
 RPL-SHA-47116-02 - Fabric Shade



FINISHES:



LINE DRAWING



WS-47116