

WAC LIGHTING

Niveous

Pendant 3000K

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-52307 7"	3000K	AB Aged Brass BN Brushed Nickel WT White	10W	777	588

Example: **PD-52307-WT**•For alternate color temperature, special order adding 27 or 35: PD-52307-35-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The Perfect sphere. Niveous reflects the smooth, frosty surface of fresh snow. Enhancing the simple purity of the flawless etched glass, Niveous offers optimized light distribution deploying multiple mid-powered LEDs to achieve an evenly lit globe with mouth blown etched triplex glass.

FEATURES

- Mouth blown etched opal glass provides even illumination
- Slope ceiling adaptable. Hang straight swivel up to 90 degrees
- Three 12 inch and one 6 inch downrods included (additional downrods available)
- Driver installed within the Junction Box, driver dimension: 3" x 1.3" x 1.2"
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-5%
Rated Life:	70,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS

RPL-GLA-52307 - Glass for PD-52307
RPL-ROD-IN06-BB - 6" rod - AB finish
RPL-ROD-IN06-BN - 6" rod - BN finish
RPL-ROD-IN06-WT - 6" rod - WT finish
RPL-ROD-IN12-BB - 12" rod - AB finish
RPL-ROD-IN12-BN - 12" rod - BN finish
RPL-ROD-IN12-WT - 12" rod - WT finish



FINISHES:



Aged Brass




Brushed Nickel



White

LINE DRAWING



WAC LIGHTING

Niveous

Pendant 3000K

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-52310 10"	3000K	AB Aged Brass BN Brushed Nickel WT White	13W	1444	1083

Example: **PD-52310-WT**•For alternate color temperature, special order adding 27 or 35: PD-52310-35-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The Perfect sphere. Niveous reflects the smooth, frosty surface of fresh snow. Enhancing the simple purity of the flawless etched glass, Niveous offers optimized light distribution deploying multiple mid-powered LEDs to achieve an evenly lit globe with mouth blown etched triplex glass.

FEATURES

- Mouth blown etched opal glass provides even illumination
- Slope ceiling adaptable. Hang straight swivel up to 90 degrees
- Three 12 inch and one 6 inch downrods included (additional downrods available)
- Driver installed within the Junction Box, driver dimension: 3" x 1.3" x 1.2"
- 5 year warranty

SPECIFICATIONS


Color Temp:	3000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-5%
Rated Life:	70,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS


RPL-GLA-52310 - Glass for PD-52310
RPL-ROD-IN06-BB - 6" rod - AB finish
RPL-ROD-IN06-BN - 6" rod - BN finish
RPL-ROD-IN06-WT - 6" rod - WT finish
RPL-ROD-IN12-BB - 12" rod - AB finish
RPL-ROD-IN12-BN - 12" rod - BN finish
RPL-ROD-IN12-WT - 12" rod - WT finish



FINISHES:



LINE DRAWING



WAC LIGHTING

Niveous

Pendant 3000K

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-52313 13"	3000K	AB Aged Brass BN Brushed Nickel WT White	13W	1437	1078

Example: **PD-52313-WT**•For alternate color temperature, special order adding 27 or 35: PD-52313-35-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The Perfect sphere. Niveous reflects the smooth, frosty surface of fresh snow. Enhancing the simple purity of the flawless etched glass, Niveous offers optimized light distribution deploying multiple mid-powered LEDs to achieve an evenly lit globe with mouth blown etched triplex glass.

FEATURES

- Mouth blown etched opal glass provides even illumination
- Slope ceiling adaptable. Hang straight swivel up to 90 degrees
- Three 12 inch and one 6 inch downrods included (additional downrods available)
- Driver installed within the Junction Box, driver dimension: 3" x 1.3" x 1.2"
- 5 year warranty

SPECIFICATIONS


Color Temp:	3000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-5%
Rated Life:	70,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS

RPL-GLA-52313 - Glass for PD-52313
RPL-ROD-IN06-BB - 6" rod - AB finish
RPL-ROD-IN06-BN - 6" rod - BN finish
RPL-ROD-IN06-WT - 6" rod - WT finish
RPL-ROD-IN12-BB - 12" rod - AB finish
RPL-ROD-IN12-BN - 12" rod - BN finish
RPL-ROD-IN12-WT - 12" rod - WT finish



FINISHES:



LINE DRAWING

