

WAC LIGHTING

Moline

Outdoor Wall Sconce 4CCT

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W17524 24"	2700K	BK Black	30W	2825	685
	3000K				
	3500K				
	4000K				

Example: **WS-W17524-40-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Crisp lines define this sophisticated wall light. Light shines through its banded diffuser creating a commanding presence on exteriors.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Light engine is factory sealed for maximum protection from the elements
- Weather resistant powder coated finish
- ACLED driverless technology
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum hardware




FINISHES:



Black

LINE DRAWING



WS-W17524

WAC LIGHTING

Moline

Outdoor Wall Sconce 4CCT

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W17532 32'	2700K	BK Black	44W	4087	925
	3000K				
	3500K				
	4000K				

Example: **WS-W17532-40-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Crisp lines define this sophisticated wall light. Light shines through its banded diffuser creating a commanding presence on exteriors.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Light engine is factory sealed for maximum protection from the elements
- Weather resistant powder coated finish
- ACLED driverless technology
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum hardware




FINISHES:



Black

LINE DRAWING



WS-W17532