

WAC LIGHTING

Doma

Pendant 4CCT

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-48516 16"	2700K	BK Black	20W	1520	1216
	3000K				
	3500K				
	4000K				

Example: **PD-48516-40-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Inner Light. A thick etched glass cylinder inside an opaline glass orb creates a luminous space for light and shadow to play across.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Featuring an Opaline outer glass and Opal Inner Glass
- Consistency of opaline glass may vary
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware

REPLACEMENT PARTS

RPL-GLA-48516-IN - INNER REPLACEMENT GLASS FOR PD




FINISHES:



Black

LINE DRAWING



PD-48516

WAC LIGHTING

Doma

Pendant 4CCT

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-48520 20"	2700K	BK Black	29W	2100	1620
	3000K				
	3500K				
	4000K				

Example: **PD-48520-40-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Inner Light. A thick etched glass cylinder inside an opaline glass orb creates a luminous space for light and shadow to play across.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Featuring an Opaline outer glass and Opal Inner Glass
- Consistency of opaline glass may vary
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware




FINISHES:



Black

LINE DRAWING



PD-48520