

WAC LIGHTING

Crescent

Pendant 4CCT

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-25410 10"	2700K 3000K 3500K 4000K	AB Aged Brass	11 W	590	532

Example: **PD-25410-40-AB**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wax and wane. Like a crescent moon playing hide and seek with the stars and slipping softly through the sky. Clear, ribbed cast glass throws lovely illumination to the room, while subtle down light is delivered from this luminaire's solid canopy.

FEATURES

- Three 12" and one 6" downrods included (additional downrods available)
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Aluminum body with ribbed acrylic diffuser

REPLACEMENT PARTS

RPL-RODIN06-886-A - 6" replacement rod for PD-2541

RPL-RODIN12-886-AB - 12" replacement rod for PD-254



FINISHES:



Aged Brass

LINE DRAWING

